





## OR U Series



Outdoor Rental LED Display



P2.6, P2.9, P3.9, P4.8













直形箱体 Straight cabinet

信号直插孔 Signal plug



弧形箱体 Curve cabinet



250x250mm  
P2/P2.5/P2.604/P3.91/P4.81/P5.95


1000U



参数Spec.



|                                   |   |
|-----------------------------------|---|
| 箱体尺寸 Size                         | 500mmX1000mmX55mm   |
| 箱体重量 Weight                       | 4.95g (铝门板/不含套件与电源/Aluminum door/Not include suite and power supply)  |
| 材质 Material                       | 铝 Aluminum  |
| 单箱套件数 Single cabinet suite number | 每箱8个模组8 modules per cabinet   |
| 安装方式 Installation                 | 吊梁吊装及固定安装 Crane girder hoisting and fixed installation  |
| 颜色 Color                          | 闪银 Silver   |
| 使用环境 Working environment          | 室内室外均可/Both indoor and outdoor  |
| 标准配件 Standard accessories         | 1个门板、1个提手、2个定位销、1.3个连接片、4套快速锁(2套快速锁+2套弧度锁)<br>1 door, 1 handle, 2 positioning pins, 1.3 Connection pieces, 4 quick locks (2 quick locks+2 Radian locks) |


细节展示 The details show


|                  |                            |                   |  |                               |
|------------------|----------------------------|-------------------|--|-------------------------------|
| 提手<br>The handle | 定位销<br>The positioning pin | 快速锁<br>Quick lock | 弧度锁 (弧形箱体)<br>Curve Lock (Curve cabinet) | 连接片<br>Connection accessories |
|                  |                            |                   |  |                               |


















## Parameters

| Item                                | P2.6                              | P2.9                              | P3.91                             | P4.81                             |
|-------------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| Pixel Pitch                         | 2.604mm                           | 2.976mm                           | 3.91mm                            | 4.81mm                            |
| LED Type                            | SMD1415                           | SMD1415/SMD 1921                  | SMD1921                           | SMD1921                           |
| Module Resolution                   | 96dots x 96dots                   | 84dots x 84dots                   | 64dots x 64dots                   | 52dots x 52dots                   |
| Driving Mode                        | 1/24scan                          | 1/21scan                          | 1/16scan                          | 1/13scan                          |
| Module Pixels                       | 9,216dots                         | 7,056dots                         | 4,096dots                         | 2,704dots                         |
| Module Size(mm)                     | 250 x 250                         | 250 x 250                         | 250 x 250                         | 250 x 250                         |
| Cabinet Size(mm)                    | 500 x 500/1000                    | 500 x 500/1000                    | 500 x 500/1000                    | 500 x 500/1000                    |
| Cabinet Resolution(dots)            | 192 x 192/384dots                 | 168 x 168/336dots                 | 128 x 128/256dots                 | 104 x 104/208dots                 |
| Pixel Density(dots/m <sup>2</sup> ) | 147,456                           | 112,896                           | 65,536                            | 43,264                            |
| Minimum Viewing Distance            | ≥2.6m                             | ≥2.9m                             | ≥3.9m                             | ≥4.8m                             |
| Brightness                          | ≥4500nits                         | ≥4500nits                         | ≥4500nits                         | ≥4500nits                         |
| IP Grade                            | IP65                              | IP65                              | IP65                              | IP65                              |
| Refresh Rate                        | 1920Hz~7,680Hz                    | 1920Hz~7,680Hz                    | 1920Hz~7,680Hz                    | 1920Hz~7,680Hz                    |
| Gray Scale                          | 12~16bits                         | 12~16bits                         | 12~16bits                         | 12~16bits                         |
| Viewing Angle                       | 160°/160°                         | 160°/160°                         | 160°/160°                         | 160°/160°                         |
| Maximum Power Consumption           | 800(W/m <sup>2</sup> )            | 800(W/m <sup>2</sup> )            | 800(W/m <sup>2</sup> )            | 800(W/m <sup>2</sup> )            |
| Average Power Consumption           | 240(W/m <sup>2</sup> )            | 240(W/m <sup>2</sup> )            | 240(W/m <sup>2</sup> )            | 240(W/m <sup>2</sup> )            |
| Inout Voltage                       | AC110V~AC220V 50Hz/60Hz           | AC110V~AC220V 50Hz/60Hz           | AC110V~AC220V 50Hz/60Hz           | AC110V~AC220V 50Hz/60Hz           |
| Operating Temperature               | -20°C~60°C                        | -20°C~60°C                        | -20°C~60°C                        | -20°C~60°C                        |
| Operating Humidity                  | 10%~90%                           | 10%~90%                           | 10%~90%                           | 10%~90%                           |
| Cabinet Material                    | Die-casting Aluminum              | Die-casting Aluminum              | Die-casting Aluminum              | Die-casting Aluminum              |
| Cabinet Weight                      | 7.5kg/panel                       | 7.5kg/panel                       | 7.5kg/panel                       | 7.5kg/panel                       |
| Operating System                    | Windows (Win7,Win8,etc.)          | Windows (Win7,Win10,etc.)         | Windows (Win7,Win10,etc.)         | Windows (Win7,Win10,etc.)         |
| Signal Source Compatibility         | DVI,HDMI1.3,DP1.2,SDI,HDMI2.0,etc | DVI,HDMI1.3,DP1.2,SDI,HDMI2.0,etc | DVI,HDMI1.3,DP1.2,SDI,HDMI2.0,etc | DVI,HDMI1.3,DP1.2,SDI,HDMI2.0,etc |