

## 43 , 55 Inch Outdoor LCD Iposter with Battery



High Light



Low Light Attenuation



High Color Rendering



Long Service Life



Good Heat Dissipation



Display Battery Level Safety&Power-saving



High-heat-resistant  
High-temperature resistant



IP65 Waterproof



Long Battery Life

---

## Structural Performance:

1. Fully galvanized steel plate housing, outer surface with imported metallic painting, anti-magnetic, anti-static, IP65 waterproof.
2. Strict electrical protection: Electrical leakage protection, overload protection, over voltage protection, lightning protection devices, overheat protection, etc.
3. Speakers: Dual-channel, stereo surround sound amplifier system, Output power: 8Ω, 2×10W.
4. Working environment: +110°~ -50°, Air-cooled structure for heat dissipation, Military-grade heat dissipation with aluminum substrate.
5. Tempered glass: 6mm AR tempered laminated glass.
6. All the systems of the entire machine adopt the modular design principle, with considerations for sustainability and maintainability.
7. Light sensing system: Automatic adjustment of ambient light brightness for anti-glare control, Images can still be clearly visible even in a strong sunlight environment.

## Product Superiority:

1. High lighting LED back lighting LCD screen, Brightness 1800nits.
2. 1920 x1080 resolution, images can still be clearly visible even in a strong sunlight environment.
3. Outdoor rainproof and heat-resistant metal housing.



## Technical Parameters

<b>Panel Parameter</b>	Panel Type	43", 55" LCD Panel
	Display Size	43" : 943×531mm ; 55" : 1209.6×680.4mm
	Display Scale	16:9
	Backlight type	Patented LED backlight modular component+Constant current source driving component
	Resolution	1080*1920
	Display Colors	16.7M
	Brightness	1800cd/m <sup>2</sup>
	Contrast	3500:1
	Visual Angle	178°(H) / 178°(V)
	Response Time	5ms
	Colors Mode	PAL/NTSC/SECAM
	Working Life	60000 hours
<b>Main board Parameter</b>	CPU	Cortex-A7 architecture, Main Frequency: 1.2G
	Memory	DDR3 1G
	Built-in storage	Support 32GB TF card maximally
	Decoding Resolution	Support 1080P maximally
	O/S	Android 7.1.1
	Network	Ethernet, WiFi
	Video Play	Support AVI(H.264、DIVX、DIVX、XVID), rm, rmvb, MKV(H.264、DIVX、DIVX、XVID), WMV, MOV, MP4(H.264、MPEG、DIVX、XVID), DAT(VCD format), VOB(DVD format), PMP, MPEG, .MPG., FLV(H.263, H.264), ASF, TS, TP, 3GP, MPG etc.
	Pictures Format	Support BMP、JPEG、PNG、GIF
	USB2.0 Port	Two USB2.0 standard port and two USB expansion port
	System Upgradation	Support upgradation by USB, SD card and remote
<b>Battery Parameter</b>	Battery	Blade battery, with long usage time and stable performance
	Charging time	7 hours
	Working time	14 hours
	Battery capacity	50000 mAh
	Input voltage	24V
<b>Working Environment</b>	Working temperature	-50°C~110°C
	Storage Temperature	-45°C~80°C
	Working humidity	10%~90%
	Storage humidity	10%~90%
	Input power supply	AC100V~240V
	Power supply consumption	≤100W

	Standby consumption	≤3W
	Housing colors	Silver, Grey, White, Black, Red
	Housing material	Galvanized steel sheet+ Outdoor painting
	Net weight	43" : 50Kg ; 55" : 65Kg
	Gross weight	43" : 58Kg ; 55" : 87Kg
	Product size	43" : 1236mm*148mm*588mm 55" : 1400mm*148mm*756mm
	Package size	43" : 1350mm*300mm*700mm 55" : 1550mm*300mm*900mm



